



|                         |               |  |
|-------------------------|---------------|--|
| Item Number             |               | STP330200100S  |
| Head                    |               | KN6033   |
| Material                |               | steel, hardened 10.9                                     |
| Surface                 |               | zinc-plated 5-7 µm, baked, blue / transparent passivated |
| Thread outside-Ø        | <b>d1</b>     | 2,00 <sup>+0,08</sup> mm                                 |
| Thread core-Ø           | <b>d2</b>     | 1,36 mm  |
| Thread-pitch            | <b>p</b>      | 0,78 mm  |
| Length                  | <b>L</b>      | 10,00 mm   |
| Head-Ø                  | <b>D</b>      | 4,00 <sub>-0,25</sub> mm                                 |
| Cylindrical head height | <b>C max.</b> | 0.35 mm  |
| Thread run-out          | <b>X max.</b> | 1,00 mm  |
| Radius                  | <b>R max.</b> | 0,80 mm  |
| H-cross recess          |               | H1   |
| Penetration Depth       | <b>t min.</b> | 0,95 mm  |
| Penetration Depth       | <b>t max.</b> | 1,25 mm  |
| Thread                  |               | STS-plus   |
| Weight                  |               | 0,184 kg/1000 pcs.                                       |
| Customs tariff no       |               | 73 181 499   |